

TECHNICAL DATA SHEET

AIMOL 2T Racekart

Fully synthetic 2-Stroke oil for karts and race engines

DESCRIPTION

AIMOL 2T Racekart is a fully synthetic 2 stroke oil especially developed for kart and race engines. The balanced additive package together with the synthetic base oil guarantee optimum results under extreme racing conditions. **AIMOL 2T Racekart** provides the best possible performance in tuned, water cooled 2 stroke race engines. Prevents sticking of the throttle valves in wet conditions. Special formulation keeps the engine free from carbon deposits and clean even at high temperatures and loads. Not to be used in injection system! Do not mix with other lubricants!

PERFORMANCE LEVELS

AIMOL 2T Racekart meets and exceeds the following performance levels/specifications:

- API/CEC-services TC+
- CIK-FIA approved lubricant for 2014 season (previously approved for 2012 and 2013 season)

AVIALABLE PACKS

Can 1 Litre
Can 20 Litre

TYPICALS FIGURES

Parameter	2T Racekart
SAE Grade	50
Density at 20°C kg/m^3	0.892
Flashpoint C.O.C. in °C	100
Viscosity at 40°C	165
Viscosity at 100°C	18.1
Viscosity Index	122
Pour Point in °C	-33

HEALTH AND SAFETY

AIMOL 2T Racekart has no adverse health effects provided it is used as directed.

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.

ANGLO INTERNATIONAL MINING B.V
Haringvliet 543, 3011 ZP Rotterdam
The Netherlands
www.aimol.nl
T +31 (0)10 28 27 927
E-mail: info@aimol.nl

Version 5/6/2015