TECHNICAL DATA SHEET

AIMOL ATF Pro 9G

Full synthetic low viscosity automatic transmission oil

APPLICATION

AIMOL ATF Pro 9G is a fully synthetic low viscosity automatic transmission oil with multi-vehicle applicability, specially tailored to meet the demands of the Mercedes Benz 9-speed NAG3 automatic transmission. It is formulated with high quality synthetic base oils to meet many European and Asian OEM specifications, ensuring wide applicability.

PERFORMANCE LEVELS

AIMOL ATF Pro 9G meets and exceeds the following performance levels/specifications:

- ZF Lifeguard fluid 6
- BMW 83 220142 516
- Aisin Warner AW-1
- DSIH 6p805
- Honda ATF DW-1
- Hyundai NWS-9638
- Hyundai SP IV, SPH-IV
- MB 236.12, MB 236.14, MB236.15, MB236.17
- Mitsubishi SP-IV
- Mitsubishi ATF-PA, ATF J13
- Nissan Matic S
- Nissan Matic W
- SAAB 93 165 147
- Toyota Type WS (JWS 3324)
- Jaso 1-A-LV
- MB236.41
- VW G 055 162, VW G 055 190, VW G 055 540

TYPICAL FIGURES

	Method	Result
Colour		Red
Density at 20°C, kg/l	ASTM D1298	0.843
Flash Point, °C	ASTM D93	174°C
Viscosity at 40 °C, cSt	ASTM D445	28.8
Viscosity at 100 °C, cSt	ASTM D445	6
Viscosity Index	ASTM D2270	161

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL ATF Pro 9G has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.