TECHNICAL DATA SHEET

AIMOL Axle Oil GL-5 LS 85W-90

Hypoid mineral gear lubricant for transmissions which require limited slip additives

APPLICATION

AIMOL Axle Oil GL 5 LS 85W-90 is a mineral hypoid gear oil to be used in heavily charged transmissions for cars that require special anti-wear protection. Contains LS (Limited Slip) additives.

PROPERTIES

AIMOL Axle Oil GL-5 LS 85W-90 has the following properties:

- Limited Slip properties
- Good protection against rust and oxidation
- Easy starting at low temperatures
- Very stable lubrication film
- Good low temperature properties

PERFORMANCE LEVELS

AIMOL Axle Oil GL-5 LS 85W-90 meets and exceeds the following performance levels/specifications:

- API-services GL5
- Mil L-2105D
- ZF TE-ML 05C/12C/16E
- MT-1

TYPICAL FIGURES

SAE Grade	85W-90
Density at 15°C kg/m3	0.904
Flashpoint C.O.C. in °C	>230
Viscosity at -12°C in cSt	1350
Viscosity at 40°C in cSt	374
Viscosity at 100°C in cSt	26.4
Viscosity Index	98
Phosphorus Content (ppm)	700
Pour point in °C	<-18

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Axle Oil GL-5 LS 85W-90 has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.