AIMOL Corstop GR 01

Oily-grease rust preventative

DESCRIPTION

AIMOL Corstop GR 01 is a general high quality rust preventive which forms a light film that provides long term protection to ferrous and non-ferrous metals.

APPLICATION

AIMOL Corstop GR 01 is designed for applications where protection is required during indoor storage for periods of twelve months. Typical applications are:

- Protection of finished machine components prior to packaging
- Protection of finished machined or ground metal surfaces such as bearings, tools, valves, rollers and fasteners
- Protection of parts during storage where thin film thickness is required

USE

AIMOL Corstop GR 01 can be applied by brushing, dipping or spraying at room temperature.
Cleaning by alkaline cleaners.

TYPICAL FIGURES

Parameter	Corstop GR 01
Appearance	Light brown
Specific gravity 20°C, gr/cm^3	0,89
Drying time, minutes	30
Type of film	Light greasy
Flash point, °C	50
Indoor protection, months	>12

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Corstop GR 01 has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.

ANGLO INTERNATIONAL MINING B.V
Haringvliet 543, 3011 ZP Rotterdam
info@aimol.nl
The Netherlands

T +31 (0)10 28 27 927
E-mail:
www.aimol.nl

MADE IN HOLLAND