# AIMOL Corstop PL 01

## Plastic-type anticorrosion and anti shock agent

***DESCRIPTION***

**AIMOL Corstop PL 01** is a solid product of plastic consistency at room temperature. Once melted, it forms a thick and elastic film on the parts of easy elimination. This anticorrosive film provides in addition great resistance to impact and abrasion.

***APPLICATION***

**AIMOL Corstop PL 01** is suitable for the protection of such as screws, valves, gears, bearings, tools, segments, car spares and machines, cutlery and springs.

***BENEFITS***

- Good protection against all kind of rust
- Easy application
- Protects from impacts and abrasion
- Easy to remove
- Safe and economic in use
- Non-toxic and risk-free under normal conditions of use
- Can be re-used

***USE***

**AIMOL Corstop PL 01** is always applied in hot, by immersion of the parts to protect in the bath that contains the melted product. Smaller films are to be applied at maximum temperature and vice versa to obtain a thicker film. It is not recommend to use temperatures above 180°C, because of the possible decomposition of the film. It is recommended to use FUSION TANK model T-1, regulated by thermostat. The temperature of the melting tank should be increased too fast.

***TYPICAL FIGURES***

| Parameter | Corstop PL 01 |
|---|---|
| Film type | Plastic, elastic, peel off |
| Colour | Light yellow, transparent |
| Temperature of use, °C | 130 - 180 |
| Spread power approx, $m^2/kg$ | 1,8 - 3 |
| Anti rust power | Limitless |
| Removal | Peeling off |
| Film thickness, mm | 1 - 2,4 |

***TECHNICAL DATA INFO LINE***

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

***HEALTH AND SAFETY***

**AIMOL Corstop PL 01** has no adverse health effects provided it is used as directed.

**DISCLAIMER**

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.