AIMOL Corstop WX 03

Waxy film anticorrosive agent

DESCRIPTION

AIMOL Corstop WX 03 is a thixotropic product with good corrosion protection. Will leave a waxy and translucent film that provides long term protection to ferrous and non-ferrous metals.

APPLICATION

AIMOL Corstop WX 03 is designed for all type of machine parts, bearings and storage parts. Typical applications include:

- Protection of packaged items during storage and shipment
- Roller bearings
- Machined and grinding automotive parts and tools

USE

To be applied at room temperature. Removal by alkaline or solvent based degreasers.

TYPICAL FIGURES

Parameter	Corstop WX 03
Appearance	Brown
Specific gravity @ 20 ºC, gr/cm^3	0,88
Viscosity @ 40 ºC, cSt	25-29
Flash point, ºC	>50
Type of film	Greasy-waxy
Indoor protection, months	12-24
Humidity cabinet, hrs	250
Salt spray, hrs	60

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Corstop WX 03 has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.