TECHNICAL DATA SHEET

AIMOL CVT Fluid

Fullsynthetic fluid for CVT transmissions.

APPLICATION

AIMOL CVT Fluid is a full synthetic transmission oil intended for the lubrication of modern Continuous Variable Transmissions (CVT).

PROPERTIES

AIMOL CVT has the following attractive properties:

- Suitable for all CVT's mentioned below;
- Optimum performance, preventing unnecessary slipping;
- Protects metal parts against wear and corrosion;
- Minimum foaming and prevents air intake.

PERFORMANCE LEVELS

AIMOL CVT Fluid meets and exceeds the following performance levels/specifications:

- BMW 83 22 0 136 376 / 83 22 0 429 154
- Chrysler CVTF+4
- CVT EZL 799 A
- Daihatsu AMIX CVT Fluid DC / CVTF DFE
- Daihatsu/Suzuki TC DEX-CVT
- Dia Queen CVTF J1
- Elf Natic CVT
- EZL-799
- Ford CVT23
- MB 236.20
- Dia Queen CVTF J4
- Mopar CVTF +4
- Nissan NS-3 / NS-2 / NS-1
- Subaru Lineartronic CVTF Ford WSS-M2C928-A
- Suzuki CVT Green 1 / CVTF Green 2 / NS-2
- Toyota CVT FE / CVT TC
- VW G 052 180 / G 052 516

TYPICAL FIGURES

Density at 15°C kg/l	0.8493
Flashpoint C.O.C. in °C	130
Viscosity at 40°C in cSt	33.6
Viscosity at 100°C in cSt	7.2
Viscosity Index	186
Pour point in °C	-42

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL CVT Fluid has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.

ANGLO INTERNATIONAL MINING B.V
Haringvliet 543, 3011 ZP Rotterdam
The Netherlands

T +31 (0)10 28 27 927
E-mail: info@aimol.nl
www.aimol.nl

MADE IN HOLLAND