TECHNICAL DATA SHEET

AIMOL Indo Gear CLP

APPLICATION

AIMOLIndo Gear CLP is an industrial gear oil with proven EP characteristics. The product is intended for use in industrial applications such as bath lubrication of heavy loaded industrial gear sets, spur, helical, bevel and worm gear configurations. High load carrying capacity which also allows absorption of sudden pressure changes and peak loads. Good prevention against rust and corrosion; good water separation.

PERFORMANCE LEVELS

AIMOL Indo Gear CLP meets/exceeds the following performance levels/specifications:

- Timken OK Load 75 lbs;
- CLP DIN 51517 part 3 CLP
- US Steel 224
- AGMA 250.04 EP/9005-D94
- FZG gear test >12
- David Brown S1.53.101

TYPICAL FIGURES

	68	100	150	220	320	460
Density @ 15 °C kg/m^3	0.891	0.893	0.898	0.900	0.902	0.903
Viscosity @ 40 °C, cSt	68	100	150	220	320	460
Viscosity @ 100 °C, cSt	9.8	11	14.8	18.8	24.2	29.8
Viscosity Index	100	100	100	100	100	100
Pour point, °C	-24	-24	-21	-21	-18	-18
Flash point, °C	224	224	240	240	251	251

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Indo Gear CLP has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.