TECHNICAL DATA SHEET

AIMOL Powerline J

Mineral Motor Oil for Petrol and Light Diesel Engines

APPLICATION

AIMOL Powerline J is a multifunctional motor oil developed for use in petrol and atmospheric aspiration diesel passenger cars and light vans with or without turbo compressor.

AIMOL Powerline J has the following attractive properties:

- Excellent cleaning of the engine;
- Anti-wear, anti-corrosion and anti-rust protection;
- Stable viscosity index;
- Dispersing and deterging properties;
- Sludge is reduced to a minimum.

PERFORMANCE LEVELS

AIMOL Powerline J meets and exceeds the following performance levels/specifications:

- API-services SJ/CF/CG-4
- ACEA A3/B3/E2
- Volvo VDS
- Volkswagen 501.01/505.00

TYPICAL FIGURES

SAE Grade	10W-30	15W-40	20W-50
Density at 15˚C kg/m3	0.882	0.871	0.889
Flashpoint C.O.C. in ˚C	>200	>200	>200
Viscosity at 40˚C in mm^2/s	74	95	155
Viscosity at 100˚C in mm^2/s	11.6	13.4	17.4
Viscosity at -15˚C in mm^2/s			>9500
Viscosity at -20˚C in mm^2/s		<7000	
Viscosity at -25˚C in mm^2/s	<7000		
Viscosity Index	149	138	>120
Pour Point, ˚C	-33	-27	<-24
TBN, mgKOH/g	6.5	6.2	6.0

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Powerline J has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.