TECHNICAL DATA SHEET

AIMOL Powerline L

Universal passenger car engine oil

APPLICATION

AIMOL Powerline L is a universal high performance engine oil for use in gasoline and diesel engines of passenger cars and light vans with or without turbo. Do not use for diesel engines with DPF (diesel particle filter)

AIMOL Powerline L has the following attractive properties:

- Very good thermal- and oxidation stability;
- Good protection against wear at cold start;
- Very good resistance against foaming, corrosion and wear;
- High dispergency and detergency level;
- Very good low temperature properties (5W-30 and 10W-40)

PERFORMANCE LEVELS

AIMOL Powerline L meets and exceeds the following performance levels/specifications:

- API-services SL/CF
- ACEA A3/B3
- ACEA A3/B4 (for 5W-30 and 10W-40)
- MB 229.1 (for 20W-50)
- VW 501.01 (for 20W-50
- VW 505.00 (for 20W-50)

TYPICAL FIGURES

SAE Grade	5W-30	10W-40	20W-50
Density at 20°C kg/m3	0.856	0.863	0.870
Flashpoint C.O.C. in °C	>200	>200	>200
Viscosity at 40°C in mm^2/s	64.0	90	145
Viscosity at 100°C in mm^2/s	10.8	13.9	18.0
Viscosity Index	158	155	138
TBN, mg KOH/g	6.4	6.4	7.0
Pour point in °C	<-36	<-39	<-36

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Powerline L has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.