TECHNICAL DATA SHEET

AIMOL Pro Line B 5W-30

Full synthetic engine oil especially developed for use in BMW/Mini engines

APPLICATION

AIMOL Pro Line B 5W-30 is a full synthetic motor oil especially developed for BMW passenger cars and light duty commercial vehicles. Also suitable for Mercedes Benz, Opel, Seat, Volkswagen, Audi and Skoda cars with regular drain intervals. AIMOL Pro Line B 5W-30 fully complies with the latest BMW Longlife-04 specification, replacing the previous generation oils. Thanks to its unique balanced formula, it provides exceptional cleanliness of parts, fuel economy, and unsurpassed protection against wear at high operating temperatures and rpm. AIMOL Pro Line B 5W-30 is suitable for cars with catalytic converters, soot filters, turbo compressed engines and direct injection systems. It has low phosphor, sulphur and sulphated ash content since it is developed on the mid SAPS technology..

AIMOL Pro Line B 5W-30 has the following properties:

- Outstanding protection to wear;
- Suitable for extremely long drain intervals (based on O.E.M. prescription);
- Unrivalled engine cleanliness and free of deposits and sludge thanks to highly active cleaning agents
- Excellent low temperature pumpability ensures that the oil reaches the lubricated parts reliably and guarantees easy engine start and protection from cold starts;
- Good anti-rust and oxidation properties.

PERFORMANCE LEVELS

AIMOL Pro Line B 5W-30 meets or exceeds the following performance levels/specifications:

BMW	Longlife -04 (approvable)
API-service	SN/CF
ACEA	C3
Fiat	9.55535-S3
Volkswagen	502.00/505.00/505.01
MB	229.31 / 229.51 /229.52
GM	Dexos 2
GM	LL -A-025 / B-25

TYPICAL FIGURES

SAE Grade	5W-30	5W-30
Density at 15°C kg/m3	ASTM D1298	0.850
Flashpoint C.O.C. in °C	ASTM D92	222
Viscosity at 40°C in mm^2/s	ASTM D445	67.2
Viscosity at 100°C in mm^2/s	ASTM D445	11.6
Viscosity Index	ASTM D2270	169
TBN, mg KOH/g (ASTM D2896)	ASTM D2896	7.4
Pour point in °C	ASTM D97	-39
MRV test at -35°C in cP	ASTM D4684	22100
CCS at -30°C in cP	ASTM D5293	<5600
HTHS, cP	ASTM D4683	3.5
Sulphated Ash wt%	ASTM D874	0.77

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Pro Line B 5W-30 has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.