TECHNICAL DATA SHEET

AIMOL Pro Line F 5W-30

Full synthetic engine oil especially developed for use in Ford engines requiring WSS-M2C-913A/B/C/D and 912A

APPLICATION

AIMOL Pro Line F 5W-30 is a full synthetic motor oil especially developed for Ford and Jaguar passenger cars and light duty commercial vehicles.
AIMOL Pro Line F 5W-30 is based HTHS (high temperature high shear) technology. This product is especially developed to meet Ford's 913C and 913D (official approval) requirements for fuel economy long-life motor oil. Allows ultra long drain intervals (up to 30.000 km depending on O.E.M. prescriptions) Also suitable for older Ford models requiring 913 A/B and all cars requiring ACEA A5/B5 and A1/B1. This oil can be mixed with both synthetic and mineral engine oils.

AIMOL Pro Line F 5W-30 has the following properties:

- Outstanding protection to wear;
- Suitable for long drain intervals (based O.E.M. prescription);
- Very stable lubrication film for cold starts;
- Good anti-rust and oxidation properties;
- Fuel saving properties.

PERFORMANCE LEVELS

AIMOL Pro Line F 5W-30 meets or exceeds the following performance levels/specifications:

- Ford WSS-M2C-913D (official approval)
- Ford WSS-M2C-913A/B/C
- Ford WSS-M2C-912A
- API SL
- ACEA A5/B5, A1/B1

TYPICAL FIGURES

SAE Grade	5W-30
Density at 15°C kg/m3	0.848
Flashpoint C.O.C. in °C	>200
Viscosity at 40°C in mm^2/s	53.5
Viscosity at 100°C in mm^2/s	9.6
Viscosity Index	165
TBN, mg KOH/g (ASTM D2896)	10.1
Pour point in °C	<-45
MRV test at -35°C in cP (ASTM D4684)	<19800
Sulphated Ash wt%	0.78

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Pro Line F 5W-30 has no adverse health effects provided it is used as directed.

DISCLAIMER
Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.

ANGLO INTERNATIONAL MINING B.V
Haringvliet 543, 3011 ZP Rotterdam
The Netherlands
T +31 (0)10 28 27 927
E-mail: info@aimol.nl
www.aimol.nl