TECHNICAL DATA SHEET

AIMOL Full synthetic motor oil for use in high power/high rpm engines/sports cars

APPLICATION

AIMOL Sportline 5W-50 is a high quality full synthetic motor oil based on PAO technology. Especially designed for use in high power/high rpm engines (sport cars). Thanks to its viscosity grade, full synthetic base and additives guarantees a quick oil circulation in all moving parts at the engine start independent of external temperatures, even under extreme conditions.

PERFORMANCE LEVELS

AIMOL Sportline 5W-50 meets or exceeds the following performance levels/specifications:

- API-services SN/CF
- ACEA A3/B4
- MB 229.3/229.1
- Renault RN0700 / RN0710
- Volkswagen 502.00 / 505.00
- BMW LL -01
- Porsche A40
- GM LL-B-025

TYPICAL FIGURES

SAE Grade	5W-50
Density at 20˚C kg/m3	0.857
Flashpoint C.O.C. in ˚C	223
Viscosity at 40˚C in mm^2/s	126
Viscosity at 100˚C in mm^2/s	19.6
Viscosity Index	178
TBN, mg KOH/g (ASTM D2896)	9
Pour point in ˚C	-42
MRV test at -30 ˚C, cP	24200
Sulphated Ash	1.16

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Sportline 5W-50 has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.

ANGLO INTERNATIONAL MINING B.V
Haringvliet 543, 3011 ZP Rotterdam
The Netherlands

T +31 (0)10 28 27 927
E-mail: info@aimol.nl
www.aimol.nl

MADE IN HOLLAND