AIMOL Streetline 10W-40

Semi-synthetic motor oil for gasoline and diesel engines of passenger cars, vans

APPLICATION

AIMOL Streetline 10W-40 is a semi-synthetic motor oil for almost all types of passenger cars with petrol or diesel engines with or without catalytic converter and/or turbocharger.
AIMOL Streetline10W-40 is especially designed for working with high loads and high temperatures, where the use of ordinary motor oil leads to an increase in the oil-consumption.

PERFORMANCE LEVELS

AIMOL Streetline 10W-40 meets or exceeds the following performance levels/specifications:

- API-Services SN/CF
- ACEA A3/B3/B4
- MB 229.1
- Volkswagen 500.00/505.00/501.01
- Fiat 9.55535-G2

TYPICAL FIGURES

SAE Grade	10W-40
Density at 15˚C kg/m3	0.861
Flashpoint C.O.C. in ˚C	210
Viscosity at 40˚C in cSt	100.4
Viscosity at 100˚C in cSt	15
Viscosity at -25˚C in cSt	<7000
Viscosity Index	157
TBN, mg KOH/g (ASTM D2896)	10.0
Pour point in ˚C	-39
MRV test at -30˚C in cP (ASTM D4684)	22700
Sulphated Ash	1.3

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Streetline 10W-40 has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.